

Product datasheet

Specifications



Rack PDU, Metered, 2U, 32A, 230V, (12) C13 & (4) C19



AP7822B

Overview

Lead time Usually in Stock

Main

Product or component type	PDU
PDU type	Metered
Cord length	3.65 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual

Complementary

Input Voltage	200 V 208 V 230 V
Height	88 mm
Width	444 mm
Output Voltage	230 V
Depth	112 mm
Net weight	3.36 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Outlet type and quantity	12 IEC 60320 C13 4 IEC 60320 C19

Environment

Product certifications	C-Tick CE GOST IRAM MIC VDE VCCI
Standards	FCC part 15 class A ICES-003
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	5.42 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 3666

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Energy efficiency

Energy Efficiency Optimized Energy efficient product

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery Yes

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



