

Product datasheet

Specifications



Custom Easy Rack Power Distribution

EPDU1000

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Colour Black
White
Red
Yellow
Blue
Orange
Grey

Product or component type PDU

PDU type Custom

Number of cables 1

Complementary

Input Voltage 230 V AC 1 phase
400 V AC 3 phases
220 V AC 1 phase
380 V AC 3 phases

Mounting location Side

Mounting preference No preference

Input Plug Type IEC 60320 C20
IEC 60309 16 A 2P + E
IEC 60309 32 A 2P + E
IEC 60309 16 A 3P + N + PE
IEC 60309 32 A 3P + N + PE
IEC 60309 63 A 2P + E
Schuko CEE 7 / EU1-16P 16 A 2P + E

Mounting mode Rack-mounted
Rack-mounted with kit

Mounting position Horizontal
Vertical

Network frequency 50/60 Hz

Number of input connectors 1

Outlet type and quantity 48 IEC 60320 C13
48 IEC 60320 C19
48 British BS 1363
48 Schuko CEE 7
48 china chinese outlet

Environment

Ambient air temperature for operation -5...45 °C

Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Contractual warranty

Warranty (in months)	12
-----------------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

 Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins