

Product datasheet

Specifications



Easy PDU Switched Zero U 32A 230V(20)C13 (4)C19 IEC309

EPDU2132S

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	2.99 m
Number of cables	1
Provided equipment	Installation guide

Complementary

Input Voltage	230 V 1 phase
Height	1650 mm
Width	56 mm
Output Voltage	230 V
Depth	62 mm
Net weight	6.65 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13

Environment

Product certifications	CE UKCA
Ambient air temperature for operation	-5...50 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.6 cm
Package 1 Width	17 cm
Package 1 Length	181 cm
Package 1 Weight	8.15 kg

Contractual warranty

Warranty (in months)	12
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	1310
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

